

> Unité de Recherche Appliquée en Energies Renouvelables, Ghardaïa – Algeria 24 - 25 Octobre 2018



Valorization of household waste via biogas production in Algeria since 1938: Inventory and Perspectives

Kheira Benaissa^{*1,2}, Belkhir Dadamoussa³, Abdelaziz Bendraoua¹

¹Département de Chimie Organique et Industrielle, Laborat<mark>oir</mark>e de Synthèse organique, Physico-chimie, Biomolécules et Environnement (LSPBE), Université des Sciences et de la Technologie d'Oran Mohamed Boudiaf, Oran, Algeria ²Laboratory of scientific research Sciences & Environment (Bio-resources, Geochemistry-physic, Legislation and socioeconomic development), Centre Universitaire de Tamanghasset

> Tamanrasset, Algeria ³University of Ghardaïa, BP 455, 47000 Ghardaïa, Algeria *Kheira.benaissa@univ-usto.dz

Le 5^{ème} Séminaire International sur les Energies Nouvelles et Renouvelables The 5th International Seminar on New and Renewable Energies Unité de Recherche Appliquée en Energies Renouvelables, Ghardaïa – Algeria 24 - 25 Octobre 2018



Abstract— Energy is an important factor in Algerian's economy, the recent Algerian's economy crisis is due to the fall of the oil incomes of 70% in less than two years, which made the country lose half of its external receipts and causing an important deficit of its trade balance. The fossil fuel reserves will not last eternally (some 40 to 50 years) and the human activity causes a significant change of the climate, which has actually important repercussions. The need to find an alternative and renewable source of energy is becoming increasingly important for the sustainable development. However, Algeria is a country rich in solar and biomass layer; according to the National Waste Agency, more than 28,219 tons of municipal solid waste are generated per day. Energetic valorization of municipal solid waste (MSW) seems to be an alternative solution for sustainable development of Algeria, which the biogas constitutes a considerable source of renewable energy. This paper presents an overview for the status of this technology in Algeria including the increasing of the interest in methanization since 1938. Also in this study, is referred the first experience of Tamanrasset (southern of Algeria) in the field of biogas production.

Keywords— biogas; municipal solid waste; renewable energies; methanization; valorization


I. INTRODUCTION

Algeria has created a green momentum by launching an ambitious program to develop renewable energies and promote energy efficiency. This program leans on a strategy focused on developing and expanding the use of inexhaustible resources, such as solar energy in order to diversify energy sources and prepares Algeria of tomorrow. Through combining initiatives and the acquisition of knowledge, Algeria is engaged in a new age of sustainable energy use. The program consists of installing up to 22 000 MW of power generating capacity from renewable sources between 2011 and 2030, of which 12 000 MW will be intended to meet the domestic electricity demand and 10 000 MW destined for export. This last option depends on the availability of a demand that is ensured on the long term by reliable partners as well as on attractive external funding. In this program, renewable energies are at the heart of Algeria's energy and economic policies: It is expected that about 40% of electricity produced for domestic consumption will be from renewable energy sources by 2030. Algeria is indeed aiming to be a major actor in the production of electricity from solar photovoltaic and solar power, which will be drivers of sustainable economic development to promote a new model of growth. The national potential for renewable energy is strongly dominated by solar and biomass energies. Algeria considers these sources of energy as an opportunity and a lever for economic and social development, particularly through the establishment of wealth and job-creating industries. The potential for wind, geothermal and hydropower energies is comparatively very small. This does not, however, preclude the launch of several wind farm development projects and the implementation of experimental projects in geothermal energy [1].

In this paper we interest to the technology of biogas, which consists in managing rationally polluting and unhealthy waste, producing energy with lower costs for cooking, heating and lighting, as well as the production of residues being able to be used for the fertilization of the agricultural or forestry lands. Biogas seems consequently an economic solution, decentralized and ecological for pollution's problems, through providing energy autonomy and sustainable development to the isolated regions and wedged as the city of Tamanrasset.

II. SOLAR ENERGY POTENTIAL IN ALGERIA

Due to its geographical location, Algeria holds one of the highest solar potentials in the world. It is valued at more than 3300 hours of sunshine per year and 05 KWh of daily energy received on a horizontal surface of 01 m^2 on most of the country [2]. The climate is largely favourable for solar energy exploitation. The objective of the strategy for developing renewable energies in Algeria was reaching to achieve, by 2015 a share of these energies in the national electricity balance that would be 6%. The total solar irradiation of the city of Tamanrasset presented in fig. 2, is measured and predicted by using the model "Third order Angström type correlation" [4].






Fig. 1 Annual average of the total solar irradiation received on the latitude of the site [3]


Fig. 2 Global solar irradiation measured and predicted with model 3 for Tamanrasset city



Since the graphic of fig. 2 of [4], the values of total solar irradiation measured and predicted for the city of Tamanrasset are in conformity. The coefficient of R^2 is higher than 0.91 and the irradiation solar peak occurs from May until July.


III. SITUATION OF MUNICIPAL SOLID WASTE IN ALGERIA

The management of solid waste in Algeria proves to be a huge problem considering the enormous quantity of household wastes produced each year through the Algerian territory. According to the National Waste Agency (AND), Algeria produces 10.3 million tons of MSW each year or 28,219 tons per day, with a collection coverage of 85% in urban areas, 60% in rural areas, a rate of 0.9 kg/ inhabitant/day for urban zones and 0.6 kg/inhabitant/ day for rural zones.



IV. WASTE MANAGEMENT SITUATION IN ALGERIA

The process of solid waste management and its energetic valorization are based on the classification of solid waste according to their composition, its categories and physicochemical characteristics. Currently, the elimination of produced waste is the solution applied to 97% in Algeria, which the solid waste is treated as follows: on a side disposed in open dumps (57%), eliminated by incineration in the open air in public dumps or municipal uncontrolled ones (30%), and controlled dumps and landfill (10%). On the other side, the quantities destined for recovery are too low: only 2% for recycling and 1% for composting [6].



Methanization is an effective mode of processing organic waste, economic and easily exploitable. This process reduces the recourse to fossil energies in the areas where the installation of natural gas and electricity is very expensive, as well as the production of a clean energy, which is biogas. In addition, this process contributes to the depollution of the organic loads, without forgetting another advantage and not the least: the production of rich manures, which can be used as an organic soil conditioner on agricultural ground poor in organic matter and for the launching of programs of afforestation intended to the reconstitution of the forest heritage. Simply, it would be necessary to target the substrates and the sites most adapted for the installation of digesters allowing a production and an optimal exploitation of biogas in Algeria.

VI. INCREASING OF THE INTEREST IN BIOGAS IN ALGERIA

Algeria is firmly committed to the promotion of renewable energy in order to provide comprehensive and sustainable solutions to environmental challenges and to the problems regarding the conservation of the energy resources of fossil origin. Algeria also plans to install some experimental size units to test the various technologies in renewable energies such as biomass, geothermal energy and desalination of brackish water.

In Algeria, the first achievements of biodigestion were carried out about the end of the Thirties, under the impulse of two teachers of the National school of agriculture of Algiers (El Harrach), Isman and Ducellier, which deposited a patent in 1938 in the United States about a system for producing a pulsating circulation in apparatus containing gas-evolving products [7]. That work has been considered as the beginning of the biogas production mastery not only in Algeria but also in the whole world.

In addition, they constructed the first digester (Fig. 5). Based on their patent, many agricultural installations were equipped with gas digesters of manure, and that various equipment of valorization of biogas had developed.




Fig. 5 The first digester constructed in Algeria [7]

Fig. 4 MSW management in Algeria [5]

V. INVOLVEMENT OF THE PRODUCTION OF BIOGAS TO SUSTAINABLE DEVELOPMENT OF ALGERIA

Unité de Recherche Appliquée en Energies Renouvelables, Ghardaïa – Algeria 24 - 25 Octobre 2018





La première voiture expérimentale de l'Institut agricole d'Algérie.

Fig. 6 The first experimental car with biogas in Algeria [8]

In 1948, and in Algeria, the first experimental car with biogas at Africa level (Fig. 6).

In 1949, an engine was developed of 08 tanks of 40 m³, supplied with 260 tons of manure (05 cattle, 12 horses and 25 pigs), and production of almost 30,000 m³ a year of biomethane until The Sixties [8]. Biogas was developed in kitchen of boarding schools (200 pupils), for the needs of the laboratory and 02 tractors.

After the discovery of less expensive fuels at the end of the Forties, the activities in the field of bio methanization decreased very quickly. A little interest was given to this technology despite the important resources and the successful applications that have been made by the National Institute of Agronomy (El Harrach) and the CDER, through the establishment of two experimental plants, in Bechar and Ben Aknoun, in 1986 and in 2001, for the study of biogas production from cow dung. Since, very few digesters were developed.

However, we must note the efforts of the Algerian government in these last years to develop this technology by upgrading the landfill of Ouled Fayet, which has been put into operation in 2011 [9]. The project's main objective is the capture of the landfill's gas, which contains 50% of methane (CH₄); the expected amount of emission reduction is 83,000 T equivalent CO_2 /year.

In addition to biomass, power projects are at the feasibility study stage such as the Sonelgaz's biomass power project in the Oued Smar site, which has an installed capacity of 02 MW that can reach a peak of 06 MW from the discharge of this site, and the energy recovery plant of biogas generated in the landfill of Batna. The sewage treatment plant of wastewater of Baraki, equipped with sophisticated processes, was put on test since the month of January 2007 with capacities for treatment of 250,000 m³ a year. Currently in Algeria, it is one of the rare stations to make function its boilers by its own biogas [10].

VII. ACADEMIC STUDIES ON BIOGAS IN ALGERIA

Since the end of the year 2001, this sector of bioenergetic production is revitalized again with Division Biomass for the

innumerable advantages, which it has. The conception and the installation of an experimental digester with a capacity of 800 liters (Fig. 7). Using cow-dung manure, the digester allowed producing 26,898 m³ of biogas during 77 days. The average composition of produced biogas is 61% of methane and 35, 65% of carbon dioxide [11].



Fig. 7 Experiment dispositif [11]

In 2007, S. Kalloum and al. [12] studied the anaerobic digestion of household wastes (waste of kitchen) and more particularly the influence of the pH on the biogas yield. The got results made it possible to show the possibility of producing a significant amount of flammable biogas for a short time for the digester with adjusted pH.

In the same year, K. Hadri and al. [13] constructed and realized a solar digester at the Research Unit in Renewable Energies in Saharan Medium of Adrar (Fig. 8). In this work the digester having a capacity of 11 liters, which the lid is a solar panel being used to supply the digester in calorific energy necessary to maintain a temperature favourable to the methanization.




Fig. 8 Solar digester of batch type without and with lid [13]

hhhhh In 2008, Nuri Azbar and al. [14] investigated the feasibility of using chemical pretreatment to improve the anaerobic biological degradation of industrial effluents containing high concentrations of phenolic compounds.

In 2009, K. Derbal and al. [15] developed an anaerobic digestion model no. 1, and model of international water association was applied to a full-scale anaerobic co-digestion process for the treatment of the organic fraction of municipal solid waste along with activated sludge wastes originating from a municipal wastewater treatment plant. This operation



was carried out in a digester of 2000 m^3 in volume. The aim of this study is to compare the results obtained from the simulation with the experimental values.

In 2012, B. Abderezzak and al. [16] developed an Excelbased spreadsheet and database program with visual basic that can help to find the optimal scenario to valorize the biogas. Finally, this scenario chosen must take into account social and environmental impacts. L. Bensmail and A. Touzi [17], in turn, interested to the Energetic valorization of the biomass: Contribution of the biogas production to sustainable development. In the same year, a research realized in Adrar, by A. Tahri and al. [18] consists in studying the production of biogas by co-digestion of organic waste (waste of slaughterhouse and poultry).

In 2014, Kalloum Slimane and al. [19] worked on the stability and the progress of the reaction from solid substrate to biogas as a final product, by the installation of batch digestion experiments. The substrate chosen in this study was slaughterhouse waste from Adrar city (southwest of Algeria). The inoculation was made by sludge issued from wastewater treatment plant. S. Maamri and M. Amrani [20] in turn, studied thermophilic anaerobic digestion of waste activated sludge (WAS) using cattle dung inoculums. The results showed that WAS mixed with cow dung is an effective feedstock for biogas production, giving a high cumulative biogas yield. The simpling of WAS was done in the urban wastewater treatment plants in Boumerdes, Algeria. In addition, M. Djaafri and al. [21] interested in improving the efficiency of biogas production with readily biodegradable substrates. The substrate chosen for this study consists of organic waste, high in sugar and cooked foods rich in starch issued from African university campus in Adrar city.

In 2015, M. Fedailaine and al. [22] studied the modeling of bio kinetics of anaerobic digestion on several aspects such as microbial activity, substrate degradation and methane production. For this, they developed a mathematical model based on mass balances on biomass, the organic substrate and biogas. Siboukeur Hicham and al. [23] made a microbiological study of the anaerobic digestion of sludge from the purifying plant wastewater from the city of Touggourt, which is southeast of Algeria. Amel Ghouali and al. [24] presented a study on an optimal control law policy for maximizing biogas production of anaerobic digesters. In addition, B. Mebarki and al. [25] developed a theoretical estimation of the production of biogas from the landfill of Batna city and its electrical conversion by a SOFC.

In 2016, Abdelbaki Mameria and al. [26] made a numerical investigation of counter-flow diffusion flame of biogashydrogen blends: Effects of biogas composition, hydrogen enrichment and scalar dissipation rate on flame structure and emissions. This study addresses numerically the influence of several operating conditions on the structure and NO emissions of a biogas diffusion flame.

VIII. BIO-ECONOMIC AND ENVIRONMENTAL MANAGEMENT WASTE MODEL CHALLENGE IN SUSTAINABLE DEVELOPMENT OF TAMANRASSET CITY: FROM WASTE TO BIOGAS ENERGY

Knowledge and scientific research is the important prerequisites for sustainable development particularly in developing countries such as Algeria, and especially in the southern regions. Knowledge in engineering systems optimization model OptiWaste, which integrate life cycle assessment (LCA) [27] is an important tool for waste companies and national authorities to avoid suboptimal environmental solutions. However, in Algeria collaboration between municipalities, households, private production sectors, is far from being a reality [28], So, one of the most important action in Tamanrasset region (Southern of Algeria), was the establishment of an effective cooperation on April 2015, between Sciences and Environment research laboratory at Tamanghasset Centre University and Direction of Environment to put-up the first biogas digester (Fig. 9) as an alternative energy strategy. Indeed, reduction in waste volume, production of biofertilizer and valuable soil conditioners it is known. That biogas process is an environment friendly, economic and an alternative means to fossil fuel. Today economy and technologies largely depend upon energy resources that are renewable as well as ecofriendly [29].

In fact, the Biogas Digester of Tamanrasset City (BDTC) with a capacity of 15m³, it is a batch type, with Chinese fixed dome (Fig. 10). The BDTC is designed to produce biogas from fermentable household waste and excrements of dromedary as microbial inoculum bio-resources for enhanced biogas production and bio-economy approach. It is made up mainly of an enclosure of digestion, impermeable and underground, which offers an anaerobic environment and a maintenance of moisture. It thus supports the methanization of a biomass biodegradable, fluid and locally available (household waste and excrements of dromedary) for biogas production. Its supply, is from the storing reservoir, is ensured by the effect of gravity. As for its partial draining. The daily supply of the digester in biomass ensures the continuity of methanization process, further than a temperature of digestion about 30°Celsius.



Unité de Recherche Appliquée en Energies Renouvelables, Ghardaïa – Algeria 24 - 25 Octobre 2018



Fig. 9 Biogas digester with a capacity of 15m³ installed at Tamanrasset city (Southern of Algeria).




Fig. 10 Digester plan: transverse section.

IX. CONCLUSIONS

The Algerian's economy is in an alarming situation. The waste management did not yet take his part of interest by the Algerian government. Algeria has a very considerable solar layer, and an enormous quantity of fermentable household waste, which these goods are not exploited yet amply.

Growth must be mastered and taking into account development consequences. We must no longer consider our goods under the sole view of immediate consumption, but also through recovery and recycling and giving these goods many lives and uses.

To take up this challenge requires an immediate awakening and a significant modification of citizen behaviors and our environmental strategy.

ACKNOWLEDGMENT

This study was carried out as a biogas initiative research project in our Sciences & Environment laboratory in Tamanghasset University Centre (Southern of Algeria); we would like to thank Mr. BOUAMER Amar, the Director of Environment of Tamanrasset city, for his collaboration.

REFERENCES

- [1] Ministry of Energy and Mines, "Renewable Energy and Energy Efficiency Program, Algiers, p. 36, March 2011.
- [2] Sonalgaz, Stratégie et Veille : Recueil trimestriel de l'hebdomadaire, n°02, DGDS/DS, 2008.

- [3] A. Benkhelifa, "Modélisation et expérimentation d'un capteur solaire plan à eau ", 2012, p.52. unpublished.
- [4] M. Nia, M. Chegaar, M.F. Benatallah and M. Aillerie, Contribution to the quantification of solar radiation in Algeria, Energy Procedia, vol 36, pp. 730 – 737, 2013.
- [5] L. Gourine, "Country report on the solid waste management: Algeria. The regional solid waste exchange of information and expertise network in Mashreq and Maghreb countries," http://www.sweepnet.org/content/algeria, 2010.
- [6] Boukelia and Mecibah, Solid waste as renewable source of energy: current and future possibility in Algeria, International Journal of Energy and Environmental Engineering. 2012, doi: 10.1186/2251-6832-3-17.
- [7] G. L. R Ducellier and M. A. Isman, System for producing a pulsating circulation in apparatus contains gas-evolving products, Algeria. Filed 03 March 1938. [Patented 26 September 1939. United States Patent Office n°2.174.203].
- [8] E. ADLER, "What is the methanization? historical, theoretical and technical backgrounds", School of Engineers of the city of Paris
 [Technical days ASTEE-EIVP, "Co-digestion of muds and other waste"]
 p. 41, 12 November 2015. unpublished.
- [9] M.A. Tabet, Types de traitement des déchets solides urbains: evaluation des coûts et impacts sur l'environnement. Revue des Energies renouvelables. Special number Production and Valorization, Biomass, pp. 97–102, 2001.
- [10] H. Zemmouri, l'eau usée vers le biogaz, CDER, bulletin 020, pp. 04–05, 2011.
- [11] S. Igoud, I. Tou, S. Kehal, N. Mansouri et A. Touzi. Première Approche de la Caractérisation du Biogaz Produit à Partir des Déjections Bovines. Revue des Energies Renouvelables. vol. 05, pp. 123-128, 2002.
- [12] S. Kalloum, M. Khelafi, M. Djaafri, A. Tahri, and A. Touzi, Study of the influence of the pH on the production of biogas from household waste. Review of Renewable Energies. vol. 10, n°4, pp. 539 – 543, 2007.
- K. Hadri, M. Khelafi, A. Boulal et N. Nedjah, conception et réalisation d'un digesteur solaire de type batch, Revue des Energies Renouvelables, CDER [ICRESD-07, Tlemcen, Algeria] pp. 97 – 100, 2007.
- [14] N. Azbara, T. Keskina, E. C. Catalkaya, Improvement in anaerobic degradation of olive mill effluent (OME) by chemical pretreatment using batch systems. Biochemical Engineering Journal, vol 38, Issue 3, pp. 379–383. 2008. doi:10.1016/j.bej.2007.08.005.
- [15] K. Derbal, M. Bencheikh-lehocine, F. Cecchi, A.-H. Meniai and P. Pavan. Application of the IWA ADM1 model to simulate anaerobic co-digestion of organic waste with waste activated sludge in mesophilic condition. Bioresource Technology. vol 100, Issue 4, February 2009, pp. 1539–1543. doi:10.1016/j.biortech.2008.07.064.
- [16] B. Abderezzak, B. Khelidj, A. Kellaci and M. Tahar Abbes. The Smart Use of Biogas : Decision Support Tool. AASRI Procedia [2012 AASRI Conf on Power and Energy Systems], vol 02, pp. 156-162, 2012. doi:10.1016/j.aasri.2012.09.028.
- [17] L. Bensmail and A. Touzi, Energetic valorization of the biomass: Contribution of the biogas production to sustainable development. Journal of Science Research, n 03, vol. 1, pp. 19-23, 2012.
- [18] A. Tahri, M. Djaafri, M. Khelafi, S. Kalloum et F. Salem. 2012. Amélioration du rendement de la production de biogaz par co-digestion des déchets organiques : déchets d'abattoir et de volaille. Revue des Energies Renouvelables. [SIENR'12 Ghardaïa, Algeria]. pp. 375 – 380, 2012.
- [19] S. Kalloum, F. Salem, A. Kouki and H. Mokaddem, Influence of inoculums/substrate ratios (ISRs) on the mesophilic anaerobic digestion of slaughterhouse waste in batch mode: Process stability and biogas production, Energy Procedia [The International Conference on Technologies and Materials for Renewable Energy, Environment and Sustainability, TMREES14] vol 50, pp. 57 – 63, 2014. doi: 10.1016/j.egypro.2014.06.007.
- [20] S. Maamri and M. Amrani, Biogas production from waste activated sludge using cattle dung inoculums: Effect of total solid contents and kinetics study. Energy Procedia, vol 50, pp. 352 – 359, 2014. doi: 10.1016/j.egypro.2014.06.042.



Unité de Recherche Appliquée en Energies Renouvelables, Ghardaïa – Algeria 24 - 25 Octobre 2018



- [21] M. Djaafri, S. Kaloum, M. Khelafi, A. Tahri, F. Salem, K. Kaidi, L. Bensmail, O. Barako, A. Kadri and A. Amrouche, Methanization of organic waste issued from African university campus in Adrar city (southwestern of Algeria). Journal of Materials and Environment Sciences. vol 05 (S2), pp. 2484-2488, 2014, ISSN: 2028-2508.
- [22] M. Fedailaine, K. Moussi, M. Khitous, S. Abada, M. Saber and N. Tirichine, Modeling of the anaerobic digestion of organic waste for biogas production, Procedia Computer Science [The 5th International Conference on Sustainable Energy Information Technology (SEIT 2015)], vol 52, pp. 730 – 737, 2015. doi: 10.1016/j.procs.2015.05.086.
- [23] H. Siboukeur, A. Touzi, A. Youcefi, M. D. Ould ElHadj, Microbiological study of the anaerobic digestion of sludge from the purifying plant wastewater from the city of Touggourt, southeast of Algeria. Energy Procedia, vol 74, pp. 172 – 176, 2015. doi : 10.1016/j.egypro.2015.07.540.
- [24] A. Ghouali, T. Sari and J. Harmand, Maximizing biogas production from the anaerobic digestion. Journal of Process Control, vol 36, pp. 79–88, 2015. http://dx.doi.org/10.1016/j.jprocont.2015.09.007.
- [25] B. Mebarkia, B. Adouane, F. Khaldi, S. Dehimi and D. Haddad, Theoretical estimation of the production of biogas from the landfill of Batna city and its electrical conversion by a SOFC. International Journal of Hydrogen Energy, vol 40, Issue 39, , pp. 13799–13805. 19 October 2015. doi:10.1016/j.ijhydene.2015.03.062.
- [26] A. Mameria and F. Tabet, Numerical investigation of counter-flow diffusion flame of biogas-hydrogen blends: Effects of biogas composition, hydrogen enrichment and scalar dissipation rate on flame structure and emissions. International Journal of Hydrogen Energy, vol 41, Issue 3, pp. 2011–2022. 21 January 2016. doi:10.1016/j.ijhydene.2015.11.035.
- [27] M. Münster, H. Ravn, K. Hedegaard, N. Juul, M. Ljunggren Söderman, Economic and environmental optimization of waste treatment, Journal of Waste Management, 2015, http://dx.doi.org/10.1016/j.wasman.2014.12.005.
- [28] A. Youb, O. Youb and H. Bouabdessalam, Sustainable solid waste management in the city of Mecheria (western Algeria), Energy Procedia, 50, pp. 953 – 959, 2014. doi: 10.1016/j.egypro.2014.06.114.
- [29] P. Merlin Christy, L.R. Gopinath and D. Divya, A review on anaerobic decomposition and enhancement of biogas production through enzymes and microorganisms, Renewable and Sustainable Energy Reviews, 34 pp. 167–173, 2014. http://dx.doi.org/10.1016/j.rser.2014.03.010.



